**R13** 

## Code No: 118EK

## JAWAHARLAL NEHRU TECHNOLOGICAL UNIVERSITY HYDERABAD B. Tech IV Year II Semester Examinations, May - 2017 SATELLITE COMMUNICATIONS

(Electronics and Communication Engineering)

Time:	3 hours Max. Marl	ks: 75
Note:	This question paper contains two parts A and B. Part A is compulsory which carries 25 marks. Answer all questions in Part A consists of 5 Units. Answer any one full question from each unit. Each question 10 marks and may have a, b, c as sub questions.	Part B carries
	32 32 PART-A 82 82 <sub>(25)</sub>	Marks)
1.a) b) c)	Define Elevation angle and write an expression for it.  List different bands along with frequency range for satellite communications.  An amplifier has a quoted noise figure of 2.5 dB. What is its equivalent temperature.	[2]
d) e)	A geographic area subtends an angle of approximately $6^{\circ} \times 3^{\circ}$ , when viewe geostationary orbit. What dimension must a reflector antenna have to illuminate his area with a circular beam $3^{\circ}$ in diameter at 11 GHz. What is mean by multiple access?	ed from alf of [3] [2]
f) g) h)	Compare TDMA and FDMA What are the different signals transmitted by GPS satellites? What are the features of GPS?	[3] [2] [3]
i) j)	List the features of pure ALOHA. List the features of slotted ALOHA.  PART - B	[2]
		Marks)
2.a) b)	Discuss the effects of sun and moon on satellite communication. Illustrate geostationary transfer orbit and AKM approach to geostationary orbit neat diagram.	using a [5+5]
3.a)	OR A low earth orbit satellite is at an altitude of 250km above the earth's surface. As earth's diameter is approximately 12,756.28km, calculate the period of when the circular. Also find the linear velocity of the satellite along its orbit.	ssuming orbit is
b)	Write short notes on solar eclipse.	[5+5]
4.a) b)	Explain the operation of a TT&C system using relevant block diagram. An earth station has a diameter of 30m, has an overall efficiency of 69% and is receive a signal at 4150MHz. At this frequency the system noise temperature when the antenna points at the satellite at an elevation angle of 28°. What is under these conditions? If heavy rain causes the rise in system noise temperature what is the new G/T value?	is 79K the G/T

5.a)	Explain the role of a transponder in satellite communication. Also draw the simplified diagram of a double conversion transponder for 14/11 GHz band.				
b)	Briefly discuss the link budget.	THE OTILE OUT		[5+5]	
6.	Explain the principle of CDMA and spread spect <b>OR</b>	rum transmissio	n and reception.	[10]	
7.a)	Assume that a TDMA system uses a 125µs fram each earth station can send within the TDMA fra preambles ii) A 5µs preamble is added at transmission. iii) A 5µs delay preamble is added 2 µs guard band is allowed between every transm	ime when i) No the beginning d to each earth s	time is lost in ov of each earth	erheads, stations	
b)	Explain the principle of FDMA.			[5+5]	
8.a) b)	Draw the block diagram of a typical earth station Explain different power test methods.	transmitter and OR	explain.	[5+5]	
9.	Discuss in detail different GPS.	OK		[10]	
10.	Explain how message is transmitted by TDMA.  OR			[5+5]	
11.a) b)	Briefly discuss the satellite packet switches. Elaborate packet reservation.			[5+5]	

---ooOoo---